


PATENT
5694-00200
1665

"EXPRESS MAIL" MAILING LABEL NUMBER
EL893867279US

DATE OF DEPOSIT AUGUST 6, 2001

I HEREBY CERTIFY THAT THIS PAPER OR
FEE IS BEING DEPOSITED WITH THE UNITED
STATES POSTAL SERVICE "EXPRESS MAIL
POST OFFICE TO ADDRESSEE" SERVICE
UNDER 37 C.F.R. § 1.10 ON THE DATE
INDICATED ABOVE AND IS ADDRESSED TO
THE ASSISTANT COMMISSIONER FOR
PATENTS, BOX PATENT APPLICATION,
WASHINGTON, D.C. 20231


Shayna Blackmar

Timer Rollover Handling Mechanism for Traffic Policing

By:

Yongdong Zhao
Craig A. Lindahl

Robert C. Kowert
Conley, Rose & Tayon, P.C.
P O. Box 398
Austin, TX 78767-0398
Ph. (512) 476-1400

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 **[0001]** This invention relates to traffic policing in communication networks, and more in particular to handling timer and policing parameter rollovers.

2. Description of the Related Art

10 **[0002]** Various communication technologies exist for transferring data across a network or between a sender and receiver. Some communication technologies may provide for the creation of one or more communication channels or paths. In some communication technologies, data may pass from source to destination through one or more switches or routers. In some applications, it may desirable to limit or police the rate
15 at which data may flow through a particular connection or channel. For example, in broadband communication networks where multiple communication channels are supported, it may be desirable to limit a channel to a particular data rate or bandwidth so that all channels may have a certain quality of service (QoS).

20 **[0003]** A network device, such as a switch, may provide traffic policing functionality to determine whether communications conform to an allocated bandwidth for each channel handled by the network device. The term “cell” is used herein to refer to any type of data unit, datagram, packet, or other data configuration communicated as a unit through a network. Traffic policing may involve monitoring the amount of data or the
25 number of cells received (e.g. by a switch) during a period of time. If too much data or too many cells are received, some of the cells may be dropped or flagged as non-conforming.

30 **[0004]** In some traffic policing devices an allowed arrival time or theoretical arrival time may be maintained for each channel. The allowed/theoretical arrival time may be set

to determine if data units are arriving too fast (e.g. too closely spaced). If a data unit (e.g. cell) arrives before the allowed/theoretical arrival time, then it may be discarded or flagged as non-conforming. If the data unit arrives after the allowed/theoretical arrival time, then it is passed on and the allowed/theoretical arrival time is incremented.

5

[0005] The traffic policing device may employ one or more counters or timers to track the actual arrival time of data units. For each channel, the traffic policing device may compare the actual arrival time to the allowed/theoretical arrival time. The timer or counter may have a certain bit width and the allowed/theoretical arrival time may be stored as a value having the same bit width as the timer or counter. For example, a 32-bit counter may be used for the timer to track actual arrival times. The allowed/theoretical arrival time may be stored as a 32-bit value.

[0006] When the counter reaches its highest value (e.g. FFFFFFFFh for a 32-bit counter), it rolls over and continues from zero. Similarly, the allowed/theoretical arrival time may rollover when it is incremented beyond its maximum value. These rollovers may cause errors in traffic policing if not accounted for. For example, if the allowed/theoretical arrival time value for a channel is large, for example FFFFFFFAh, and the timer counter rolls over, then the arrival time of a data unit may appear small, for example 00000005h. When the arrival time is compared to the allowed/theoretical arrival time, if rollover is not accounted for, the arrival time will appear to be less than the allowed/theoretical arrival time indicating that the data unit arrived too early (when in fact, in this example, it arrived eleven clocks after the allowed/theoretical arrival time). Similarly, if the allowed/theoretical arrival time is incremented beyond its max value so that it rolls over and a data unit arrives before the arrival time counter rolls over, it may appear that the data unit is conforming (since the arrival time appears to be greater than the allowed/theoretical arrival time), when in fact the data unit may have arrived too early.

[0007] In some communications systems, the network device, switch, router, etc. that is performing a traffic policing function may be configured to handle a large number of channels. For example, a switch may handle thousands of different channels. The switch may store and maintain a different allowed/theoretical arrival time and other traffic parameters for each channels. The allowed/theoretical arrival time may roll over independently for each channel. Also, a roll over of the arrival time counter may effect all of the channels at once. The more channels handled by a device, the more difficult it may be to account for roll overs of the arrival time counter and the allowed/theoretical arrival time for each channel.

10

Exhibit A-1

SUMMARY OF THE INVENTION

5 [0008] A network traffic policing device may employ a conformance algorithm to determine whether to accept or discard incoming data cells. For each communication channel handled by the network policing device, policing parameters (e.g. assigned traffic parameters and historical traffic data) may be stored in a memory table for use by the conforming algorithm. When a new data cell is received, the stored data for that cell's communication channel may be retrieved from the table and be used by the conformance algorithm.

10

15 [0009] The network policing device may include a timer configured to provide a timer value for use by the conformance algorithm in determining whether received cells are conforming or non-conforming. An arrival time from the timer value may be determined for each cell and compared against the policing parameters for the cell's communication channel to decide whether to accept or discard (or flag) an incoming cell. The timer value has a maximum value that, when reached, the timer value starts over at 0 (i.e., rolls over). The network policing device is configured to account for such rollovers of the timer value when comparing a cell's arrival time (a timer value) to the policing parameters. Also, a policing parameter may have a maximum value and may rollover when incremented beyond that maximum value. The network policing device may also be configured to account for rollovers of a policing parameter when determining whether or not a cell is conforming.

25 [0010] Each communication channel entry in the table may also include rollover data configured to indicate a rollover phase relationship between the timer value and a theoretical arrival time policing parameter. The rollover data may indicate for each communication channel if the theoretical arrival time has rolled over ahead of the timer value, is behind the timer value in rollover phase, or is in rollover phase with the timer value. The rollover data may be updated at least once per rollover phase of the timer.

The rollover data may also include an indication of the timer phase at the last time the rollover data was updated.

[0011] In one embodiment, the network traffic policing device may include a global timer phase indicator. In one embodiment, the global timer phase indicator may be viewed as a 1-bit extension to the global timer. Thus, the global timer phase indicator may be toggled each time the timer rolls over and provides an indication of the current rollover phase of the timer. When accessing a communication channel entry in the table (whether as part of an update process or as part of a traffic policing conformance process) the global timer phase indicator may be compared to the rollover data to determine if the rollover data has been updated for the current phase of the timer.

[0012] At least once per timer rollover phase an update process may be performed on the rollover data for each communication channel entry in the table. Also, for each data cell received by the network device, the global timer phase indicator may be compared to the rollover data for that cell's communication channel to determine if the rollover data needs to be updated before the network device determines whether or not the cell is conforming according to its arrival time and policing parameters. Thus, communication channel rollover data entries that have not yet been updated by the update process may be updated before determining whether or not a cell is conforming. After the network device determines whether or not a cell is conforming, the theoretical arrival time policing parameter is updated for that cell's communication channel entry in the table. If the theoretical arrival time update causes the theoretical arrival time value to roll over, then the rollover data for that table entry is updated to reflect the theoretical arrival time value rollover.

[0013] In one embodiment the network policing device also performs network operations and maintenance (OAM) activities. Each entry in the table may also include OAM data used in performing the operations and maintenance activities. The network device may perform an OAM table scan periodically in which the OAM data in each table

entry is read and possibly modified according to alarm conditions, etc. In one embodiment, since the OAM table scan is performed more frequently than the timer rolls over, the rollover data update process may be performed as part of or in conjunction with the OAM table scan. The network device may include a global timer rollover indicator that is set when the timer rolls over. When a operation and maintenance table scan is initiated, the global timer rollover indicator may be checked to determine if the rollover data has been updated since the last OAM table scan. Thus, if the global timer rollover indicator is set, a rollover data update process is performed with the OAM process for each table entry. Upon completing an entire table scan in which the rollover data is updated, the global timer rollover indicator is cleared.

[0014] In one embodiment, a network device may include a cell processing unit configured to receive incoming data cells from a network for a number of communication channels. The network device may have a timer configured to provide a timer value to the cell processing unit. The network device may also include a memory coupled to the cell processing unit and configured to store one or more policing parameters and rollover data for each of the communication channels. The rollover data may include an indication of a rollover relationship between the timer value and one of the policing parameters for each of the communication channels. For each received incoming data cell, the cell processing unit is configured to assign an arrival time from the timer value and compare the received incoming data cell's arrival time to the one or more policing parameters for the received incoming data cell's communication channel to determine if the received incoming data cell is conforming or non-conforming to a rate for the communication channel. The cell processing unit is configured to access the rollover data for the received incoming data cell's communication channel to account for the rollover relationship when comparing the arrival time to the one or more policing parameters.

[0015] In one embodiment, the timer is configured to increment the timer value at a predetermined frequency and the timer value rolls over to zero and continues incrementing upon reaching a maximum timer value. The policing parameters may

include a theoretical arrival time that may roll over upon being incremented past a maximum value. The rollover data may indicate for each communication channel whether or not the timer value and theoretical arrival time are in the same rollover phase.

- 5 **[0016]** In one embodiment, the network device may include a timer rollover phase indicator configured to indicate a current rollover phase of the timer value. The cell processing unit is configured to access the memory to perform an update of the rollover data for each communication channel at least once per rollover phase of the timer value.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] Figure 1 illustrates an example of a network system, according to one embodiment;

5

[0018] Figure 2 is a block diagram of components that may be included within a network device for traffic policing, according to one embodiment;

[0019] Figure 3 illustrates policing parameter and rollover data entries in a memory table, according to one embodiment;

10

[0020] Figure 4 illustrates a method for updating rollover data associated with each communication channel handled by a network device, according to one embodiment;

[0021] Figures 5A, 5B and 5C, illustrate a method for processing newly arrived cells in a network device which accounts for arrival time and policing parameter rollovers, according to one embodiment;

15

[0022] Figure 6 illustrates a network device which may be configured to route or switch cells for a plurality of communication channels, according to one embodiment;

20

[0023] Figure 7 illustrates a channel table that may include policing parameters, rollover data, and operations and maintenance data for each channel, according to one embodiment;

25

[0024] Figure 8 illustrates a method for indicating global timer rollovers and rollover phase version in a network traffic policing device, according to one embodiment; and

[0025] Figure 9 illustrates an operation and maintenance scan which includes updating rollover data for each communication channel handled by a network device, according to one embodiment.

30

[0026] While the invention is described herein by way of example for several embodiments and illustrative drawings, those skilled in the art will recognize that the invention is not limited to the embodiments or drawings described. It should be understood, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

DETAILED DESCRIPTION OF EMBODIMENTS

5 [0027] Turning now to Figure 1, an example of a network system is illustrated. The network system may include various subscribers or endpoints 102 coupled to a network 100. An endpoint 102 may be a subscriber device such as a computer system or telephony device or other type of user device such as a personal digital assistant (PDA), mobile phone, set-top box, workstation, personal computer, or any other endpoint device configured for communicating data through a network to another device. An endpoint device 102 may also be a server or other type of device for supplying data in response to requests received through network 100. Network 100 may include network devices 104 for communicating data transmissions from one endpoint device 102 to another endpoint device 102. Network devices 104 may be routers, switches, multiplexers, or any other type of device configured for participating in the formation of communication channels in a network.

15 [0028] Each network device 104 may include one or more input ports for coupling to other network devices 104 and/or endpoints 102. Each network device 104 may also include one or more output ports for connecting to one or more other network devices 104 or endpoints 102. An endpoint device 102 may send a data communication to be sent through network 100 to another endpoint 102. The communication may include one or more data units, datagrams, cells, packets, etc. The term "cell" is used herein to refer to any type of data unit, datagram, packet, or other data configuration communicated as a unit through network 100. A network device 104 may receive cells at its input ports and route or switch each cell to its appropriate output port, for example, according to address information or other routing or switching information included with or within each cell. In some embodiments each physical port on a network device 104 may handle multiple different communication channels (e.g. broad band communication). In other embodiments each physical port may handle only a single communication channel.

processing unit 208 may access a memory 210 to obtain traffic policing parameters for each channel. Note that only components related to traffic policing are illustrated, however, the network device may include other components for routing or switching cells, some of which may be included in cell processing unit 208.

5

[0032] When cell processing unit 208 receives a cell it may access a location in memory 210 corresponding to the communication channel for the received cell. The memory location may store a theoretical arrival time and possibly other policing parameters for that communication channel. Cell processing unit 208 may compare the arrival time of the cell as provided by global timer 202 to the policing parameters from memory 210 in order to determine if the just-received cell is conforming to the particular cell rate for that communication channel. Cell processing unit 208 may then calculate a theoretical arrival time for the next cell to be received on that channel and store that theoretical arrival time value in the channel's location in memory 210. Due to implementation limitations, the theoretical arrival time values stored in memory 210 and calculated by cell processing unit 208 may have a maximum value size. For example, the theoretical arrival time may be calculated and stored as a 32-bit value in one embodiment. In other embodiments the maximum size of the theoretical arrival time may be larger or smaller than a 32-bit value. As the theoretical arrival time value is incremented by cell processing unit 208 as new cells are received, it may eventually reach the maximum value and rollover from zero – similar to the value provided by counter 204.

[0033] For ease of comparison, the arrival time supplied by counter 204 and the theoretical arrival time stored in memory 210 may both have the same maximum value size. However, if either the counter 204 or the theoretical arrival time for a particular channel has rolled over since the last cell was received for that channel, the fact that a rollover has occurred must be taken into account when the next cell is received to ensure a proper comparison. For example, if the theoretical arrival time value for a channel is large, for example FFFFFFFFAh, and the timer counter rolls over, then the arrival time of a data unit may appear small, for example 000000005h. When the arrival time is compared

to the allowed/theoretical arrival time, if rollover is not accounted for, the arrival time will appear to be less than the theoretical arrival time indicating that the data unit arrived too early (when in fact, in this example, it arrived eleven clocks after the allowed/theoretical arrival time). Similarly, if the allowed/theoretical arrival time is incremented beyond its max value so that it rolls over and a data unit arrives before the arrival time counter rolls over, it may appear that the data unit is conforming (since the arrival time appears to be greater than the allowed/theoretical arrival time), when in fact the data unit may have arrived too early.

10 **[0034]** To account for rollovers in the global timer value and the theoretical arrival time value, rollover data may be stored in memory 210 for each channel. The rollover data for each channel may indicate if the global timer value has rolled over ahead of the theoretical arrival time value, or if the theoretical arrival time value has rolled over ahead of the global timer value, or if the two values are in the same rollover phase. When a new
15 cell is received, the cell processing unit 208 may access memory 210 to obtain the policing parameters and rollover data for that cell's channel. The rollover data may be used to ensure that any rollovers are taken into account when comparing the cell arrival time obtained from global timer 202 to the theoretical arrival time for the cell obtained from memory 210. For example, if the rollover data indicates that the global timer value
20 has rolled over ahead of the theoretical arrival time value, then processing unit 208 knows to treat the arrival time value as being greater than the theoretical arrival time even though the 32-bit value from counter 204 may be smaller than the 32-bit theoretical arrival time value (note that 32-bit values are merely one example).

25 **[0035]** In response to either the counter 204 rolls over or the theoretical arrival time value calculated for a particular channel rolls over, the corresponding rollover data in memory 210 may be updated. As cell processing unit 208 calculates new theoretical arrival times for each channel it may update the rollover data in memory 210 for that channel as rollovers occur. However, a rollover by counter 204 may affect all channels
30 handled by network device 104. A network device 104 may handle a large number of

channels. For example, in one embodiment a network device 104 may be an ATM (Asynchronous Transfer Mode) switch handling 64K channels. When counter 204 rolls over it may take a certain amount of time to update the rollover data for each channel. New cells may be received before the rollover data has been updated for all channels after a global timer rollover. Global timer 202 may include version identifier (VerID) 206. The global timer version identifier 206 provides an indication of the current phase or version of the global timer. In one embodiment the global timer version ID 206 is a global register bit that is toggled each time counter 204 rolls over.

10 **[0036]** The rollover data stored in memory 210 for each channel may include an update version indicator to indicate whether or not the rollover data for that channel has been updated since the last global timer rollover. When a new cell is received, the update version from the rollover data for that channel may be compared to the global VerID bit 206 to determine if the rollover data is current. If the rollover data is current then cell processing unit 208 may proceed with its traffic policing function using the global timer value and policing parameters from memory 210. If the rollover data is not current then the rollover data is first updated to reflect that the global timer 202 has rolled over, and then cell processing unit 208 proceeds with traffic policing. In embodiments in which VerID 206 and the update version information of the rollover data are single bit values, then when counter 204 rolls over the rollover data for all channels is updated before another rollover of counter 204 occurs.

[0037] Turning now to Figure 3, an example of entries in memory 210 for each channel is illustrated. Memory 210 may store policing parameters 302 for each channel. For example, the policing parameters may include a theoretical arrival time value (TAT), an increment value (I) and a limit value (L). The theoretical arrival time may be calculated according to the cell rate that has been negotiated, set, or otherwise configured for the particular channel. For example, a channel may be a constant bit rate channel for which a maximum cell rate has been negotiated, e.g., 1K cells per second. The policing parameter I corresponds to the amount by which the theoretical arrival time may be

incremented after each cell is received. For example, if the channel has a 1K cell/second rate, then I may equal one millisecond. The policing parameter L may represent a limit during which a cell may be received early and still be considered conforming. Thus, if a cell is received within L of the TAT it may be conforming.

5

[0038] A channel may also be a variable bit rate channel in which case a sustained cell rate (SCR), a peak cell rate (PCR), and a burst tolerance (BT) may have been negotiated or assigned. The sustained cell rate may indicate an average allowable cell rate over a long period of time. The peak cell rate may indicate a maximum cell rate for the channel. And the burst tolerance may indicate the maximum size of back-to-back cells that may be sent on the channel at the peak cell rate. The theoretical arrival time may be calculated according to these values to determine whether or not each incoming cell is conforming or non-conforming. An example of how theoretical arrival times may be calculated in one embodiment is according to the Asynchronous Transfer Mode standard as defined by the ATM forum and the ITU (International Telecommunications Union). *See, e.g.*, Traffic Management Specification, Version 4.1, ATM Forum, March 1999; ITU-T Recommendation I.371, "Traffic Control and Congestion Control in B-ISDN," ITU-T Study Group 13, Geneva, August 1996; ITU-T Recommendation I.356, "B-ISDN ATM Layer Cell Transfer Performance," ITU-T Study Group 13, Geneva, October 1996; and ITU-T Recommendation I.361, "B-ISDN ATM Layer Specification," ITU-T Study Group 13, Geneva, November 1995. It is noted that the present invention may be adapted for other types of communication technologies besides ATM that employ traffic policing in which rollovers of arrival time and traffic parameter values are encountered, such as Frame Relay, IP Intserv, IP Diffserv, Multiprotocol Label Switching (MPLS), and Switched Multimegabit Data Services (SMDS).

25

[0039] Memory 210 may also store rollover data 304 for each channel. In one embodiment rollover data 304 may include an R bit, B bit, and V bit. The B bit is set to indicate that the current theoretical arrival time is behind the global timer phase. In other words the B bit is set when the global timer counter rolls over ahead of the theoretical

30

arrival time. The R bit is set to indicate that the theoretical arrival time has rolled over ahead of the global timer. R and B are both set to zero to indicate that the theoretical arrival time and global timer are in the same rollover phase. The V bit indicates an update version for each channel. The V bit may be compared to the global VerID bit 206 to determine if the R and B bits for that channel have been updated according to the current phase of the global timer 202. Note that the R, B and V bits are only one example of an encoding to indicate the rollover relationship and/or update status. Any encoding or data representation may be employed that indicates the rollover relationship between the timer and theoretical arrival time. Such alternative representations may also indicate their update status. Note also that theoretical arrival time is only one example of the type of traffic for which rollover conditions may be handled according to the present invention.

[0040] Turning now to Figure 4 a method for updating the rollover data associated with each communication channel handled by a network device (e.g. switch) is illustrated. The method may be implemented by hardware, software, or a combination of hardware or software within a network device 104. In one embodiment, the method of Figure 4 may be implemented as part of cell processing unit 208. The method functions to update the rollover data stored in memory 210 for each communication channel handled by the network device 104. In one embodiment this update process may be triggered each time global timer 202 rolls over. In other embodiments the update process may be performed independently of global timer rollovers as long as the update process is performed at least once for each phase of the global timer so that the global timer does not roll over twice before the rollover data entries for each channel are updated in memory 210.

[0041] In one embodiment when the global timer 202 rolls over, as indicated at 400, the global register bit VerID 206 is toggled as indicated at 402. Thus, the global register bit VerID 206 provides an indication of the current phase of the global timer. To perform the rollover data update, the rollover data for a channel is accessed from memory 210 as indicated at 404. The rollover data may include a V bit which indicates the phase of the global timer at the last time the rollover data for this channel was updated. The V bit is

compared to the global VerID bit 206 as indicated at 406. If the V bit is equal to the VerID bit then the rollover data has already been updated for the current global timer phase. The process may then continue for the next channel as indicated at 416.

5 **[0042]** If the rollover data V bit is not equal to the VerID bit then the rollover data for that channel needs to be updated. The V bit is then set to equal the current VerID bit 206 to indicate that the rollover data for that channel is now updated, as indicated at 408. The rollover data may be updated by determining whether or not the R bit of the rollover data is set, as indicated at 410. If R is set then that indicates that the theoretical arrival time
10 value had previously rolled over ahead of the global timer value. Now that the global timer has rolled over, the global timer and theoretical arrival time are both in the same phase. Thus, R is reset to zero, as indicated at 412, and the process may continue for the next channel, as indicated at 416. If R is not set then that indicates that either the global timer and theoretical arrival time were both previously in phase or that the theoretical
15 arrival time was previously behind the global timer in rollover phase. Either way, now that the global timer has rolled over the theoretical arrival time is behind the global timer in rollover phase so B is set to one, as indicated at 414, to indicate that the theoretical arrival time for this channel is behind the global timer in rollover phase. The process then continues for the next channel as indicated at 416.

20 **[0043]** As mentioned above, the update process for rollover data for each channel may be triggered when the global timer rolls over. Alternatively the update process of 404 through 416 may be performed independently from global timer rollovers where rollover data for each channel is updated at least once per global timer rollover phase so
25 that the global timer does not rollover twice before rollover data for any channel is updated.

30 **[0044]** Turning now to Figures 5A-5C a method for processing newly arrived cells in a network device is illustrated which accounts for rollovers according to one embodiment. The method of Figures 5A-5C may be implemented by cell processing unit

208. When a new cell is received, as indicated at 500, the policing and rollover data for the channel on which the cell was received may be accessed, as indicated at 502. The method includes determining whether or not the rollover data has been updated for that channel, as indicated at 504. If the V bit of the rollover data is equal to the VerID global register bit 206 then the rollover data is current and cell processing continues as illustrated in Figure 5B. If the rollover data is not current (V not equal to VerID) then the rollover data must first be updated before cell processing continues. The V bit is set to equal the global VerID bit as indicated at 508 and the R or B bit is updated as indicated at 510-514.

10
[0045] When the rollover data has been updated for the cell's channel, cell processing continues as illustrated in Figure 5B. The policing and rollover data may be used to determine if the received cell is conforming or non-conforming to the bandwidth established for the cell's channel. The R bit of the rollover data may be examined, as indicated at 518, to determine if the channel's theoretical arrival time value is ahead of the cell's arrival time (value from global timer 202). If R equals one, then the cell's arrival time was earlier than the theoretical arrival time since the theoretical arrival time is ahead of the global timer in rollover phase. According to one embodiment, the cell may be still be considered to be conforming if it arrived within a limit amount L from the theoretical arrival time. Thus, if the cell's arrival time is greater than or equal to the theoretical arrival time (taking rollover into account) minus L, then the cell may be considered conforming as indicated at 520 and 524. The theoretical arrival time is then updated for that channel, as shown in Figure 5C. If the cell's arrival time is not greater than or equal to the theoretical arrival time minus L, then the cell has arrived too early and may be considered non-conforming as indicated at 520 and 526.

[0046] If R is not equal to one (at 518), then the B bit of the rollover data is examined as indicated at 522. If B is equal to one, then the channel's theoretical arrival time is behind the cell's arrival time (from global timer 202) in rollover phase. Thus, if B equals one, the cell has arrived after the theoretical arrival time for the cell's channel and the cell

may be considered conforming, as indicated at 528. The theoretical arrival time for the cell's channel may then be updated, as shown in Figure 5C. If B is not equal to one (at 522), then the cell's arrival time and the theoretical arrival time are in phase in regard to rollover. If the cell's arrival time is greater than or equal to the theoretical arrival time minus L, as indicated at 530, then the cell may be considered conforming, as indicated at 532. The channel's theoretical arrival time may then be updated, as indicated at 536 and in Figure 5C. If the cell's theoretical arrival time is not greater than or equal to the theoretical arrival time minus L then the cell has arrived too early and may be considered non-conforming, as indicated at 534.

10

[0047] If a cell is considered conforming then normal cell processing may continue for that cell as is appropriate for the particular network technology. For example, in one embodiment network device 104 may be an ATM switch. The ATM switch may be configured to handle multiple (e.g. 64K) ATM virtual channels. If a cell is considered non-conforming, the cell may be dropped. Alternatively, if the network device 104 (e.g. ATM switch) has sufficient bandwidth it may flag the cell as non-conforming and still continue processing of the cell. Later network devices receiving a flagged cell may then be free to drop the cell since it has already been determined to be non-conforming.

[0048] The theoretical arrival time is incremented for each channel as a conforming cell is processed, as shown in Figure 5C. If the current theoretical arrival time for the channel is greater than the cell's arrival time then the theoretical arrival time is updated by adding an increment I to the current theoretical arrival time, as indicated at 538. If the cell's arrival time is greater than or equal to the theoretical arrival time, then the theoretical arrival time is updated by setting the theoretical arrival time to equal the cell's arrival time plus the increment I, as indicated at 540. If updating the theoretical arrival time (538 or 540) causes the theoretical arrival time value to rollover, as indicated at 542, then the rollover data for that channel is updated to reflect the theoretical arrival time rollover. If the B bit equals one (indicating that the theoretical arrival time was behind the global timer in rollover phase) then B is reset to zero (546) to indicate that the

theoretical arrival time and global timer are now in phase for this channel. If B is not equal to one (544) then R is set to one (548) to indicate that the theoretical arrival time has now rolled over ahead of the global timer.

5 **[0049]** As discussed in regard to Figure 4, the rollover data for each communication channel handled by the network device is updated at least once per rollover phase of the global timer 202 in one embodiment. This rollover data update process may be a stand alone-process. However, in other embodiments the rollover data update process may be optionally performed as part of (or piggy-backed with) another process that is performed
10 at least once per global timer rollover phase. For example, the network device 404 may also perform alarm and maintenance activities for each channel. The memory locations in memory 210 for each channel may also include alarm and maintenance data for each channel. An alarm and maintenance process may scan through the channel table in memory 210 reading and possibly modifying the alarm and maintenance data for each
15 channel entry as it cycles through the channel table in memory 210. This alarm and maintenance channel table scan may be performed periodically at a rate so that it is performed at least once per global timer rollover phase. For example, in one embodiment the alarm and maintenance channel table scan is performed every 0.5 seconds and the global timer value may be from a 32 bit counter clocked at 100 megahertz which rolls
20 over approximately once every 43 seconds. Thus, the rollover data update process may be performed as part of the alarm and maintenance channel table scan process.

[0050] Figure 6 illustrates a network device 600 which may be configured to route or switch cells for a plurality of communication channels. The network device 600 may
25 include a scanning function unit 610 configured to perform alarm and maintenance activities for the plurality of communication channels. The scanning function unit 610 may also update rollover data for each channel as part of its alarm and maintenance scan function. The network device 600 may also include a cell processing and policing unit 612 configured to determine if incoming cells are conforming or non-conforming
30 according to policing parameters for each channel. A memory arbitration unit 614 may

be included for arbitrating access to memory 616 between scanning function unit 610 and cell processing and policing unit 612. A global timer 602 may provide a global timer value from counter 604 to the scanning function unit 610 and the cell processing and policing unit 612. The global timer 602 may also provide a global VerID bit 606 which indicates the current rollover phase of the global timer value. Global timer 602 may also provide a global timer rollover indicator (GTRI) 608. The global timer rollover indicator 608 may indicate if the global timer has rolled over since the last channel table scan was performed by scanning function unit 610. Note that VerID 606 and GTRI 608 may also be implemented separate from global timer 602. Memory 616 may include a channel table storing policing parameters, rollover data, and alarm and maintenance parameters for each channel.

[0051] Figure 7 illustrates the channel table that may be stored in memory 616. The table may include policing parameters 702 and rollover data 704 for each channel. The policing parameters may include a theoretical arrival time, increment value, and limit value for each channel as described in regard to Figures 2-5C. The rollover data may include bits for indicating the rollover phase relationship of the global timer value and the theoretical arrival time for each channel and for indicating the update version of the rollover data for each channel, such as the R-B-V bits described in regard to Figures 2-5C. Each channel table entry may also include operation and maintenance data 706.

[0052] The operations and maintenance (OAM) data may be used by the network device to perform OAM functions to monitor the availability and performance of the communication channel connections. OAM functions may include Alarm Indication Signal (AIS), Remote Defect Indication (RDI), continuity check (CC), etc. When the network device detects a fault on a communication channel connection, it may generate and send an AIS signal in the continuing/forward direction to the next network device connected on the other end of the connection. Similarly when the network device receives an AIS on a communication channel, it may generate and send an RDI in the reverse/return direction to the network device connected on the other end of the

connection. If the network device continues to detect a fault, it may generate and send the AIS periodically as long as the faults exist. In one embodiment, the AIS shall be sent at a rate of 1 AIS per second.

5 **[0053]** The OAM functions may be implemented by scanning the table in memory 616. In the table, there may be an AIS bit for each communication channel. When a table scan detects the AIS bit is set to 1, an AIS signal is generated for the communication channel. The table may be scanned periodically, for example at the rate of one round per second in one embodiment. During the table scanning process, the AIS bit of each
10 communication channel is examined one by one. If AIS=1 is seen for a communication channel, an AIS is generated for that communication channel. When the network device detects faults, it sets the AIS bit in the table to 1 for all the communication channels that are affected. After the faults have been cleared, the network device may reset those AIS bits to 0. In one embodiment, the OAM functions are Asynchronous Transfer Mode
15 (ATM) OAM functions as defined by the ATM Forum and/or International Telecommunications Union (ITU) ATM standards.

[0054] When the global timer value rolls over, the VerID 606 is toggled and the global timer rollover indicator 608 is set, as indicated at 800 and 802 in Figure 8. As
20 discussed above, scanning function unit 610 may perform an operations and maintenance (OAM) scan of the channel table in memory 616. This table scan may be performed at least once per global timer rollover phase. Figure 9 illustrates an operation and maintenance scan which includes updating the rollover data for each channel. At the beginning of an operation and maintenance scan 900 the global timer rollover indicator
25 608 may be checked as indicated at 902. If the global timer rollover indicator 608 is not set then the regular operation and maintenance functions are performed for each channel as indicated at 917 and 919. If the global timer rollover indicator 608 is set then the rollover data may be updated (904-914) along with performing the operation and maintenance functions (916) for each channel (918). After the channel table in memory
30 616 has been completely scanned, the global timer rollover indicator 608 is cleared as

indicated at 920. The rollover data update (904-914) may be performed as described in regard to 404-414 of Figure 4.

[0055] In another embodiment, the global timer rollover indicator (GTRI) 608 may be checked during an operations and maintenance table scan before performing the operation and maintenance functions for each channel to determine whether or not a rollover data update needs to be performed. The current channel being scanned when the global timer rollover indicator 608 is first determined to be set may be marked and when the operations and maintenance scan cycles completely through the channel table back to the marked channel, the global timer rollover indicator 608 may be cleared.

[0056] The rollover data update and cell conformance processing may be summarized as follows.

(1) Initialization

15 R=0, B=0, TAT=Timer Value, V=VerID=0, GTRI=0.

(2) R-B-V Update

When the global timer rolls over, toggle VerID, set GTRI=1, start to update R-B-V fields. After the update is completed, reset GTRI=0

20 If V=VerID, skip to next table entry

If V≠VerID, do the following.

{V=VerID.

If R=1, set R=0

Else set B=1.}

25

(3) Conformation test

Let T_a be the arrival time of the current cell. If V≠VerID, update R-B-V first.

(3.1) If R=1, (TAT is ahead of T_a in clock phase which means that $T_a < TAT$)

If $T_a \geq TAT - L$, conforming $TAT = TAT + I$.

30 Else non-conforming

(3.2) If B=1, TAT is behind the T_a in clock phase.

Conforming, B=0 and $TAT = T_a + I$,

(3.2) If R=0 and B=0, TAT and T_a are in the same clock phase.

If $T_a \geq TAT - L$

35 {Conforming.

If $T_a \geq TAT$, $TAT = T_a + I$.

Else $TAT = TAT + I$.

}

Else non-conforming.

(3.4) If TAT rolls over
 {If B=1, set B=0.
 Else set R=1
 }

5

[0057] Various modifications and changes may be made to the invention as would be obvious to a person skilled in the art having the benefit of this disclosure. It is intended that the following claims be interpreted to embrace all such modifications and changes and, accordingly, the specifications and drawings are to be regarded in an illustrative rather than a restrictive sense.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
220